



## Enterprise-Grade Internet Service

LTE Routers  
 Cellular Service  
 Enterprise Management Platform  
 App for Individual Use



### Connect

Your devices to the internet over cellular & fixed wired line, instantly



### Protect

Your home, small business, boat, or RV with built-in cellular back-up and advanced security features



### Control

Your network from anywhere with Simplifi's native app and cloud-based remote management platform

## Be resilient in work & play:

Far more than a hotspot Simplifi, has all your home and small business connectivity needs covered.



**Resiliency**  
Built in fail-over so you never lose connection again!



**Security**  
IPsec, UAM/RADIUS, SPI/Firewall, port forwarding, cellular to ethernet connection



**Connected**  
Complete network in a box. 32 WiFi Connections, connected to fixed wire line and/or LTE, 4G, 3G, 2G



**Simplicity**  
Plug n' play, set and forget  
Remote management platform for easy configuration



**Portability**  
No moving parts, no external antennas, works anywhere there is cellular connection



**Reliable**  
24 hour support, Enterprise grade solution

## Ready to join The Resiliency?

### Contact

Sales@Simplifi.io  
239-919-8551

#### Networks

BS6425L-A-11  
LTE FDD: B2/B4/B12  
WCDMA: B2/B4/B5

BS6425L-AF-11  
LTE FDD: B2/B4/B5/B12/B13/B14/B66/B71  
WCDMA: B2/B4/B5

BS6425L-AU-11  
LTE FDD: B1/B2/B3/B4/B5/B7/B8/B28  
LTE TDD: B40  
WCDMA: B1/B2/B5/B8  
GSM: B2/B3/B5/B8

BS6425L-E-11  
LTE FDD: B1/B3/B5/B7/B8/B20  
LTE TDD: B38/B40/B41  
WCDMA: B1/B5/B8  
GSM: B3/B8

BS6425L-G-11  
LTE FDD: B1/B2/B3/B4/B5/B7/B8/B12/B13/B18/B19/B20  
B25/B26/B28  
LTE TDD: B38/B39/B40/B41  
WCDMA: B1/B2/B4/B5/B6/B8/B19  
GSM: B2/B3/B5/B8

BS6425L-V-11  
LTE FDD: B4/B13

#### Data Speeds

LTE - FDD CAT4 Max 150Mbps (DL), Max 50Mbps (UL)  
DC-HSPA+ DL 42 Mbps  
HSUPA - UL 5.76Mbps

#### WLAN

Dual-Band/ 802.11 b/g/n/ac, WPA / WPA2/WPA2 Enterprise

#### USB (3.0)

USB (Host) HS and FS

#### LAN

(10/100/1000 Base-T)

RJ-45 Modular Jack on side panel for TCP / IP, PPP, UDP

#### SIM

1.8V and 3.0V standard USIM (2FF)

#### LED Indicators

Cellular network status (1 ea.)  
LAN traffic (1 ea.)  
USB traffic (1 ea.)

#### Power Supply Requirements

120/240 VAC at 10VA (10W) max

#### Outline Dimensions

(Less AC prongs and mounting tab)

4.1" (104mm) Height  
2.2" (56mm) Width  
2.0" (51mm) Depth

#### Weight

7 oz (198 g)

#### Operating Temperature

-10°C to +40°C

#### Storage Temperature

-30°C to +70°C

#### Approvals

PTCRB, 3GPP  
FCC parts 2 and 15  
CE, TUV