

## Cosmolon® Hook and Loop 100% nylon woven



Tape width 5/8", 3/4", 1", 1.5", 2", 4" \*

Put-Ups 50yds/Roll \*

Color Black (580), White (501) \*

Peel/Shear Strength# 1.20lbs/inch / 16.50lbs/inch2

NFPA 1951;1971;1975;1977;1999;2112

**Oeko-Tex Standard** 

## Cosmolon® Fire Retardant Hook and Loop 100% nylon woven with flame retardant back coating

Certification



Tape width 5/8", 3/4", 1", 1.5", 2", 4" \*

Put-Ups 50yds/Roll \*

Color Black (580), Beige (C001) \*

Peel/Shear Strength# 1.00lbs/inch / 16.00lbs/inch2

Certification FMVSS 302, FAR-25.853a

NFPA 1951;1971;1975;1977;1999;2112

## Cosmolon® Soft Hook 100% nylon woven



Tape width 5/8", 3/4", 1", 1.5", 2", 4" \*

Put-Ups 50yds/Roll \*

Color Black (580), White (501) \*

Peel/Shear Strength# 0.42lbs/inch / 27.47lbs/inch2

Certification Oeko-Tex Standard

## Cosmolon® Unnapped Loop 100% nylon woven



Tape width 5/8", 3/4", 1", 1.5", 2", 4" \*

Put-Ups 50yds/Roll \*
Color Black (580) \*

Peel/Shear Strength# 0.42lbs/inch / 27.47lbs/inch2

Certification Oeko-Tex Standard



# All initial data was collected in YKK labs. Individual testing may yield different results.

\*Any other width, put-ups and color are available upon requests.

Fabrication service available

Please visit our website for more information

YKK (U.S.A.) Inc. 770-427-5521

