

THE **AD230 AGROWDRILL** IS ALL ABOUT VERSATILITY. IT OFFERS A RANGE OF INNOVATIONS TO MAKE SOWING EASIER, AND ADDITIONAL OPTIONS SO IT CAN BE CUSTOMISED FOR YOUR FARM

If you're looking for a machine that can offer all the innovation and reliability of the Agrowdrill range, with the additional versatility to help get the job done faster, then look no further than the AD230 Agrowdrill.

The AD230 is all about versatility with the right balance of strength and power. It's built on the same tough frame that makes Agrowdrills so long-lasting and offers a high capacity, dual compartment seed box so you can sow for longer without stopping.

Additionally, the working width reaches the length of the frame offering greater efficiency and superior trash handling.





PRACTICAL VERSATILITY

The AD230 is available in a range of row and tyne spacing configurations. And with a range of additional optional features, it's never been easier to customise your seeding platform to suit the conditions of your farm.

EASY MONITORING

The AD230 has shaft rotator indicators built into the front of the drive assembly. They offer easy visual confirmation that your machine is operating correctly - all you have to do to check is glance at the machine.

ROBUST DRIVE SYSTEM

The chain drive system is directly coupled to the stub axle. It's dependable variable speed gearbox and dog clutch system engages when the drill is lowered and disengages when the drill is lifted. It's one less worry when turning the drill while sowing.

OPTIONS

- Coulters
- Double chuting
- Small seeds box
- · Small seed flexi-chute
- Harrows
- Press wheels
- Rear tow hitch
- Rubber tyred roller
- Flexiroller
- Implement trailer

SPECIFICATIONS

RANGE		16 Row	20 Row	24 Row	24 Row	28 Row
Undercarriage		425 Coil Tyne with Baker Boot				
Tyne Spacing		225mm	150mm	125mm	150mm	125mm
Working Width		3.6m	3m	3m	3.6m	3.5m
Transport Width		3.7m	3.25m	3.25m	3.7m	3.7m
Hopper Capacity	Front	710L	605L	605L	710L	710L
	Rear	710L	605L	605L	710L	710L
Tyre Size		11.5/80-15.5 Implement Tyres				
Number of Toolbars		4				
Toolbar Spacings		442mm				
Under Frame Clearance		620mm				
Drawbar Power		100-130hp	80-100hp	100-130hp	100-130hp	100-130hp
Linkage Type		Trailing with hydraulic lift				

SPECIFICATIONS MAY CHANGE WITHOUT NOTICE



AGROVPLOW®

Prosperity through Soil Care.

Contact your local dealership

Your local dealer is:

www.agrowplow.com.au