

# AD730 AGROWDRILL

PRECISION PERFORMANCE  
**ROW AFTER ROW**  
**SEASON AFTER SEASON**

**AGROW**PLOW®

THE AD730 AGROWDRILL IS FEATURE-PACKED AND HAS STRENGTH TO MATCH. OUR TOUGHEST DRILL WILL DELIVER SEED EXACTLY WHERE YOU NEED IT TO BE, ROW AFTER ROW, SEASON AFTER SEASON

At Agrowplow we pride ourselves on developing products that consistently deliver the performance and reliability you need to improve crop prosperity. With the AD730 we didn't hold back. We threw in all the features we could think of and then we went and showed it to farmers like you to ask what else they need.

The result is a seed drill that's stronger, more precise, and more reliable. The range of undercarriage options means you can customise the AD730 to suit your farming operations, from high penetration in hard soils with the heavy-duty spring tyne to minimum tillage operations with the double disc unit. The huge hopper volume and high floatation tyres mean you can get the job done in fewer passes, reducing compaction and maintaining soil structure for future seasons.







### YOUR FARM, YOUR WAY

The AD730 is available in a range of configurations to suit your needs. The heavy-duty spring tyne and 720mm clearance provide superior versatility and trash handling, while the Double Disc Unit enables maximum accuracy for minimum tillage operations.

### LONGER LASTING

The heavy-duty spring tyne has a huge 250kg breakout, so nothing gets between you and the end of the row. And with our 100x100x9mm RHS frames and Agrowplow's ongoing product support, your drill will keep running season after season.

### HIGHLY CUSTOMISABLE

Agrowplow offers a range of options so you can modify your AD730 to suit conditions on your farm. Increase soil contact and finish with harrows and press wheels, and add versatility with our small seeds boxes and flexi chutes. Visit our website for a full list of options.

### OPTIONS

- Coulters
- Double chuting
- Small seeds box
- Small seed flexi-chute
- Harrows
- Press wheels
- Rear tow hitch
- Rubber tyred roller
- Flexiroller
- Implement trailer

## SPECIFICATIONS

RANGE		18 Row	22 Row	20 Row	24 Row	28 Row
Undercarriage		551 HD Spring Tyne, 251 Spring Tyne, 401 Double Disc Unit				
Tyne Spacing		225mm	225mm	175mm	175mm	175mm
Working Width		4.05m	4.95	3.5m	4.2m	4.9m
Transport Width		4.87m	5.75m	4.35m	5.05m	5.75m
Hopper Capacity	Front	880L	1080L	755L	920L	1080L
	Rear	880L	1080L	755L	920L	1080L
Tyre Size		380/85R24				
Number of Toolbars		4				
Toolbar Spacings		550mm				
Under Frame Clearance	551 HD Tyne	720mm				
	251 Spring Tyne	630mm				
	401 Double Disc	630mm				
Drawbar Power		120-150hp	130-180hp	120-150hp	130-160hp	150-200hp
Linkage Type		Trailing with hydraulic lift				

SPECIFICATIONS MAY CHANGE WITHOUT NOTICE

Contact your local dealership



**AGROWPLOW®**  
Prosperity through Soil Care.

[www.agrowplow.com.au](http://www.agrowplow.com.au)

Your local dealer is:

