

Prestressed Concrete Bridge Design Seminar

Session 1 – April 13, 2021

2a. Fabrication of Prestressed Concrete Girders



1


Overview

Economical fabrication depends on economical design and detailing

- Process and details of fabrication
- Design considerations (later presentations)

Much info from *PCI Bridge Design Manual*

- Chapter 2 – Material Properties
- Chapter 3 – Fabrication and Construction
- Chapter 4 – Strategies for Economy




Many fabrication details are possible – a few examples are shown

2

2

Prestress Plants



3

Materials

Prestressing strand


Mild reinforcement

Concrete

4

4


Prestressing Strand



Prestressing strand
ASTM A416 Grade 270



Strand shipped in coils




Pretensioned strands and
post-tensioning anchorages, spirals and ducts
*Pretensioning and post-tensioning can be
combined as shown here*


5

5


Mild Reinforcement



REBAR @ ENDS
- - STRANDS
- - REBAR @ ENDS



REBAR @ C
- - STRANDS
- - REBAR @ ENDS



6

6

Concrete

Conventional methods for proportioning and mixing concrete

- High strength mixes – up to 10 ksi at 28 days
- High flow mixes to move through congested reinforcement
- Rapid strength gain so girders can be removed from the beds quickly



Aggregate conveyor



Batch plant discharge

7

7

Fabrication

- Forms
- Casting beds
- Strands – straight & harped
- Tensioning & ducts
- Embedments
- Casting operations

8

8


Forms

- External
 - Side forms
 - Soffit
 - End headers
 - Adjustable forms
 - Internal void forms
 - Self stressing bed
- Internal
 - Stay-in-place
 - Removable


9

9

External Forms



Girder side forms



Box beam form

10

10


Adjustable Forms

Some prestressers use adjustable forms

Form to adjust top flange width



Horizontal joint allows insertion of filler or haunched sections



Other form modifications will be discussed later



11

11

Soffit or Pallet Forms

The soffit is the form for the bottom of the girder

- Defines the width of bottom flange
- Supported by and attached to supports




12

12

End Forms

Headers are usually fabricated of steel to allow reuse

- Avoid modifying strand patterns
- Slotted for draping strands
- Wood may be used if modifications are required



Bulb-tee end form (header)




Modification required for skewed ends

13

13

Stay-In-Place Internal Forms



Voided slab form

Waxed cardboard void forms for cored slab



Polystyrene foam billet for trapezoidal box beam – also for conventional box beams

14

14

Removable Internal Forms



Placing expanded form for RR box beam



Void form for cylinder pile



Removing retracted void form

15

15

Self-Stressing Forms

Form structure resists the pretensioning force - no abutments required


- Strand anchor plates bear on form

Square Piling Form



Double-Tee Form

- Similar to NEXT Beam



16


16

Prestressing Bed

The structure that resists the pretensioning force on the strands

Abutment type bed – most common

- Abutments are typically fixed in foundation
- Slab may be used as strut between abutments
- Typical bed length: 300 – 500 ft long; can be ≤ 200 ft




Details for multi-strand tensioning are shown

17

17

Abutments



Tied



Cantilever – most common

18

18

Strutted-Type Bed

Raised structural elements resist forces



Pile sections used as struts



Strands are in top flange for haunched pier segments of spliced girder bridges

- Struts provide reaction for strands anchored at level of strut



Strands at top of haunched segment

19

19

Strand Anchor Plates

Anchor plates span between abutments – major structural elements

- Strand pattern is set – 2 in. x 2 in. grid is standard
- Assembly can usually be raised or lowered as needed



20

20

Strand Anchor Plates

Self-stressing piling form

- Strand pattern is set using heavy end plates
- NEXT Beam is similar



21

21

Strand Anchorage

Strand chucks

- Reusable type is standard
 - Spring-loaded at stressing end
 - May use non-spring-loaded at dead end
- Single use
- Strand splice



22

22

Single Strand Tensioning

Strands are tensioned from one end of bed
Single strand tensioning with long ram



Elongation measurement



Elongation and pressure gage readings must agree within 5%

Pressure gages on pump




Elongation for 500 ft bed is 42.6";
25.6" for a 300 ft bed

23

23

Multi-Strand Tensioning & Detensioning



24

24

Multiple Strand Tensioning & Detensioning




Separate anchorages for top (draped) and bottom (straight) strands



Stressing rams behind the abutments pull large rods to stress strands

25


Straight Strands



26

26

Draped Strands – Hold Down



Hold down anchored to rail under bed



27

Draped Strands – Hold Up

External A-frame supports hold-up

Internal plate assembly supported on pallet inside bed

28

28

Draped Strands – Hold Up

Example of internal plate hold up device

Crane lift point

Pin

In lowered position

In raised position

Rollers

29

29

Stressing Strands

All strands are tensioned in 2 steps

- Initial tension of 2000 to 4000 lbs, depending on bed length
 - Removes slack and seats dead end chuck
 - Provides reliable starting point for QC readings
- Remaining stress is then applied to full tension
 - For Grade 270 0.6-in.-diam. strands = 43.9 kips
- Corrections may be needed for abutment movement, chuck seating, and temperature

Draped strands will have different forces or elongations from straight strands, adding complexity to stressing operations

30

30

Debonding

Plastic sleeve or tubing prevents bond between strand and concrete

- Option for stress control at ends of girders instead of draping
- Preferred over draping by most fabricators
- May also be used for top strands in center portion of girder

Installation

- Must access strands to place and seal with tape
- Not all strands are easily accessible
- Ends of sleeves sealed to prevent entry of concrete


31

31

Debonding

Material

- Two-piece snap together sleeves
 - Easy to use
- Solid tube
 - Placed on strand as installed in bed
 - Not as easy to install
- Split sleeve (not allowed by some DOTs)
 - Has to be taped for full length to prevent concrete from entering sleeve
- Ends of all types of sheath must be sealed
- If sheath is not continuous, joints must also be taped



32

32

Debonding Considerations

For economical design, engineers need to understand how girders are manufactured in a plant


- Provide minimum debond length required by design to control stresses
- Stagger terminations of debonding to avoid potential cracking
- Consider access when selecting debonded strands
 - Workers must access strands to apply and seal debonding
 - Special attention may be required for NEXT beams where side forms are fixed and strands can only be accessed from above
 - Discuss with local fabricators

33



33

Embedments

Bearing plates and diaphragm holes



Additional bars used to secure hole form



Form and pipe hangers

34

34

Quality Control

Bed setup



Stirrup spacing



Cross-section dimensions

35

35

Quality Control

Mix development & concrete testing



Concrete strength testing



Slump test

36

36

Concrete Delivery and Placement

Concrete delivered to and placed in forms

- Various methods used
- Units shown do not agitate the concrete, which is delivered by auger



Concrete delivery



Concrete placement

37

37

Concrete Delivery and Placement

Vibration is typically used to consolidate concrete

Self-consolidating concrete (SCC) or high slump concrete is often used

- Facilitates placement, promotes good consolidation, and reduces vibration requirements



Internal vibration



External (form) vibration

38

38

Top Flange Finishes

Typically the top flange receives a raked finish with minimum amplitude of $\frac{1}{4}$ in. for composite behavior

May be partial width if partial depth prestressed deck panels are used



39


39

Curing

Curing is important

- Forms are typically covered to retain temperature and moisture

Accelerated (elevated temperature or steam) curing may be used



Curing tarps are used to retain heat for initial curing

Theoretical time-temperature curve for accelerated curing

40

40


Detensioning

Initial concrete strength, f'_{ci} , must be achieved before detensioning

Tarps and side forms are removed

Single strand detensioning

- Workers simultaneously detension each strand according to pattern in shop drawings
- Strands are heated with a torch until wires relax and break – they are not cut
- Specified procedure and pattern
- Hold downs must be released to avoid damage as girders shorten and camber



41

41

Detensioning

Gang detensioning

- Re-pressurize rams
- Release hardware holding load, then depressurize rams
- Girders will move down bed as they are detensioned
- Since girders move, hold downs must be released to avoid damage
 - May lead to high stresses in girders before strands are detensioned
 - If so, may require additional reinforcement or other measures

42

42

Detensioning

Girders camber up and the ends slide on the bed as they are detensioned

- Initial camber measurements are often made while still on bed
- Fabricators may lift girder ends before taking camber reading to relieve any drag force at ends

Sliding can cause spalling at the ends of a girder

- Bearing plates help prevent spalling
- Skewed ends on bottom flange should be avoided

43

43

Finishing Girder Ends



Strands extending from girder after transfer



Strands burned off with short projections on ends cast into diaphragm



Strands cut flush & sealed on ends at expansion joints



Foam recess form for cutting and patching strands

44


44

Quality Control

Post-Pour Non-Conformance Report

Job	Worksheet	Name	Date
Product Type, Mark & Position No. 1			
Product Type, Mark & Position No. 2			
Product Type, Mark & Position No. 3			
Product Type, Mark & Position No. 4			
Product Type, Mark & Position No. 5			
Product Type, Mark & Position No. 6			
Product Type, Mark & Position No. 7			
Product Type, Mark & Position No. 8			
Product Type, Mark & Position No. 9			
Product Type, Mark & Position No. 10			
Product Type, Mark & Position No. 11			
Product Type, Mark & Position No. 12			
Product Type, Mark & Position No. 13			
Product Type, Mark & Position No. 14			
Product Type, Mark & Position No. 15			
Product Type, Mark & Position No. 16			
Product Type, Mark & Position No. 17			
Product Type, Mark & Position No. 18			
Product Type, Mark & Position No. 19			
Product Type, Mark & Position No. 20			
Product Type, Mark & Position No. 21			
Product Type, Mark & Position No. 22			
Product Type, Mark & Position No. 23			
Product Type, Mark & Position No. 24			
Product Type, Mark & Position No. 25			
Product Type, Mark & Position No. 26			
Product Type, Mark & Position No. 27			
Product Type, Mark & Position No. 28			
Product Type, Mark & Position No. 29			
Product Type, Mark & Position No. 30			
Product Type, Mark & Position No. 31			
Product Type, Mark & Position No. 32			
Product Type, Mark & Position No. 33			
Product Type, Mark & Position No. 34			
Product Type, Mark & Position No. 35			
Product Type, Mark & Position No. 36			
Product Type, Mark & Position No. 37			
Product Type, Mark & Position No. 38			
Product Type, Mark & Position No. 39			
Product Type, Mark & Position No. 40			
Product Type, Mark & Position No. 41			
Product Type, Mark & Position No. 42			
Product Type, Mark & Position No. 43			
Product Type, Mark & Position No. 44			
Product Type, Mark & Position No. 45			
Product Type, Mark & Position No. 46			
Product Type, Mark & Position No. 47			
Product Type, Mark & Position No. 48			
Product Type, Mark & Position No. 49			
Product Type, Mark & Position No. 50			
Product Type, Mark & Position No. 51			
Product Type, Mark & Position No. 52			
Product Type, Mark & Position No. 53			
Product Type, Mark & Position No. 54			
Product Type, Mark & Position No. 55			
Product Type, Mark & Position No. 56			
Product Type, Mark & Position No. 57			
Product Type, Mark & Position No. 58			
Product Type, Mark & Position No. 59			
Product Type, Mark & Position No. 60			
Product Type, Mark & Position No. 61			
Product Type, Mark & Position No. 62			
Product Type, Mark & Position No. 63			
Product Type, Mark & Position No. 64			
Product Type, Mark & Position No. 65			
Product Type, Mark & Position No. 66			
Product Type, Mark & Position No. 67			
Product Type, Mark & Position No. 68			
Product Type, Mark & Position No. 69			
Product Type, Mark & Position No. 70			
Product Type, Mark & Position No. 71			
Product Type, Mark & Position No. 72			
Product Type, Mark & Position No. 73			
Product Type, Mark & Position No. 74			
Product Type, Mark & Position No. 75			
Product Type, Mark & Position No. 76			
Product Type, Mark & Position No. 77			
Product Type, Mark & Position No. 78			
Product Type, Mark & Position No. 79			
Product Type, Mark & Position No. 80			
Product Type, Mark & Position No. 81			
Product Type, Mark & Position No. 82			
Product Type, Mark & Position No. 83			
Product Type, Mark & Position No. 84			
Product Type, Mark & Position No. 85			
Product Type, Mark & Position No. 86			
Product Type, Mark & Position No. 87			
Product Type, Mark & Position No. 88			
Product Type, Mark & Position No. 89			
Product Type, Mark & Position No. 90			
Product Type, Mark & Position No. 91			
Product Type, Mark & Position No. 92			
Product Type, Mark & Position No. 93			
Product Type, Mark & Position No. 94			
Product Type, Mark & Position No. 95			
Product Type, Mark & Position No. 96			
Product Type, Mark & Position No. 97			
Product Type, Mark & Position No. 98			
Product Type, Mark & Position No. 99			
Product Type, Mark & Position No. 100			

Post-pour inspection



Product tracking

RFID tag




45

45

Fabrication Defects and Repairs

PCI Repair Manual (MNL 137-06)



This guide helps provide a uniform assessment and approach to fixing many defects to ensure that responses are measured, appropriate and cost-effective for the situation.

Currently being updated

Discussed in later presentation

46

46

Handling and Transportation

Plant Handling and Storage

- Lift points
- Storage & stacking

Transportation

- Trucking
- Barge
- Rail




47

47

Lifting and Storage

Lifting loops and other lifting devices



Typical strand loops

Rigid lifting devices

Sling

48

48

Lifting and Storage

Stacking & Storage



Precast deck panels



Girders on dunnage in plant



49

49

Shipping

Stacking & Storage



Loading girder on a truck

Specialized equipment is used




50

50

Shipping

Remotely steered trailer



51

51


Shipping Considerations

Increase overhang over supports to improve stability

- Need to consider stresses
- Full f'_c is usually available by time of shipping

Several methods to attach girder to hauling equipment

- Fabricator may request holes through web or flange



52

52

Shipping Considerations

Shipping route

- Will load be permitted on route?
- Length of girder for curves and obstacles
- Roll stiffness of the hauling system
- Consider superelevation along route
- Access to the site

If questions – discuss with fabricator and/or hauling contractors

Issues related to lateral stability are discussed in later presentation

53

53

Shipping Record Length Girders



NU Girder 65m (210 ft)
December 2001



210 ft long single-piece girder - NU 2800 (110 in.)

54

54

New Record Longest Single-Piece Girder in US


Mod WSDOT WF100G – 223 ft long at CL; add 7 ft for skew
- LWC was used to reduce weight for hauling



See article in Fall 2019 issue of *ASPIRE* 55


55

Barge & Rail



56

Installation



57

Launching Beam or Truss

Setting precast beam with launching beam

- Crane lifts girder from truck and sets on dolly on the launching beam
- Truck backs up to push girder across launching beam where it can be picked by crane at other end



58

58

Launching Beam or Truss

Launching beam on steroids in Oregon



59

59

Launching Beam or Truss

Placing one end of girder on dolly on launching beam

Truck will back up to push it across launching beam



60

60

Launching Beam or Truss



Two cranes lift girder while dollies are repositioned

61

61

Launching Beam or Truss



Motorized dollies move girder across the launching beams to the next span

Photos are from the late Dr. Keith Kaufman with Knife River PS in OR

62

62

Launching Beam or Truss

Using load triangle to pass girder between two cranes



63

63


Launching Beam or Truss

Using load triangle to pass girder between two cranes



64

Shoring



65

Summary

Keys to economical prestressed concrete bridges

- Understanding production of girders
- Proper design and detailing
- Local availability of products
- Repetitive use
- Open communications

Contact your local fabricators!

66

Crane Lifting

Pop quiz!!

Why are they having to use a come-along along to set this girder?

- Girder is being set with a single crane with inclined leads
- Far end of girder is higher, so it is already on the bearing
- Inclined pick on this end creates thrust



67

67

Prestressed Concrete Bridge Design Seminar

Session 1 – April 13, 2021

2a. Fabrication of Prestressed Concrete Girders

Questions?



68
