



ULTRASUN
RECHARGE YOURSELF

PRODUCT LEAFLET



E5

2020-2021



AVAILABLE COLOURS



Dream White
Metallic



Fancy Red
Metallic

CONTROL SYSTEMS



Wireless
Management
System



Paytronic

* When placing the Ultrasun E5 make sure that the device is surrounded by 10-15 centimetres of free space for air circulation.

* The dimensions indicate an open Ultrasun E5.

STANDARD EQUIPPED WITH



Solar
Control



Electronic
Ballasts



TopCooler



Music



Handles



Changing
Cubicle



CollaTan
Lamps

ADDITIONAL OPTIONS

LAMP SPECIFICATIONS

ULTRASUN E5

NON-EU | UV4

Total Lamps	30 x Sunfit RXL 120W E-Tronic 190 cm or 30 x Sunfit XL 180W E-Tronic 190 cm
Maximum exposure time	15 minutes

EU | UV3

Total Lamps	30 x Sunfit XL3 120W DUO 190 cm or 30 x Sunfit XL3 180W E-Tronic 190 cm
Maximum exposure time	20 minutes



TECHNICAL SPECIFICATIONS

E5 120W

Power supply	3 x 400V + N + PE 50/60 Hz
Plug and cable	16 CEE 5 x 2,5 mm ²
Power	4.000W
Breaker/fuse (slow)	3 x 16A
Minimum net weight ¹	175 kg
Minimum crated weight ¹	215 kg
Boxed dimensions	227 x 114 x 120 cm

E5 180W

Power supply	3 x 400V + N + PE 50/60 Hz
Plug and cable	16 CEE 5 x 2,5 mm ²
Power	5.900W
Breaker/fuse (slow)	3 x 16A
Minimum net weight ¹	180 kg
Minimum crated weight ¹	220 kg
Boxed dimensions	227 x 114 x 120 cm

¹ Minimum weight is based on an Ultrasun E5 with standard configuration. Machine specific weight information available on request.



Granaatstraat 6
7554 TR Hengelo
The Netherlands



+31 (0)74 2912215



info@ultrasun.nl



Ultrasuninternational.com