

STANDARD EQUIPPED WITH

Control



Age Control



Lamps



TopCooler



VibraPlate



ADDITIONAL OPTIONS



Cubicle



Manager



Air Extraction Hose



224cm 178cm 135cm

CONTROL SYSTEMS



Ultrasun Manager



Paytronic



Wireless Management System

AVAILABLE COLOUR



Sunny Silver Metallic

- * When placing the Ultrasun i8 make sure that the device is surrounded by 10-15 centimetres of free space for air circulation.
- * The dimensions indicate an open Ultrasun i8.

LAMP SPECIFICATIONS

ULTRASUN 18 LIMITED EDITION


EU UV3	
Total Lamps	48 x Sunfit XXL3 200W CollaTan E-Tronic 200 cm
Maximum exposure time	20 minutes (CHECK)



TECHNICAL SPECIFICATIONS

ULTRASUN 18 LIMITED EDITION

Power supply	3 x 400V + N + PE 50/60 Hz
Plug and cable	16A CEE 5 x 2,5 mm ²
Power	9.200W
Breaker/fuse (slow)	3 x 16A
Minimum net weight ¹	225 kg
Minimum crated weight ¹	265 kg
Boxed dimensions	227 x 114 x 125 cm



¹ Minimum weight is based on an Ultrasun i8 with standard configuration. Machine specific weight information available on request.







info@ultrasun.nl







