



ULTRASUN
RECHARGE YOURSELF

PRODUCT LEAFLET



i8

2020-2021



AVAILABLE COLOURS



Dream White
Metallic



Xtreme Orange
Metallic

CONTROL SYSTEMS



Ultrasun
Manager



Paytronic



Wireless
Management
System

* When placing the Ultrasun i8 make sure that the device is surrounded by 10-15 centimetres of free space for air circulation.
* The dimensions indicate an open Ultrasun i8.

STANDARD EQUIPPED WITH



IQ Touch
Control



Age
Control



Electronic
Ballast



TopCooler



VibraPlate



Handles



Music Pro



Wellness
Sound



Voice
Guide



Bluetooth



Rainbow
Manager



Air
Extraction
Hose

ADDITIONAL OPTIONS



Breeze

+



Aroma



Airco



Changing
Cubicle



CollaTan
Lamps

LAMP SPECIFICATIONS

ULTRASUN i8

NON-EU | UV4

Total Lamps	48 x Sunfit XXL 200W E-Tronic 200 cm
Maximum exposure time	12 minutes

EU | UV3

Total Lamps	48 x Sunfit XXL3 200W E-Tronic 200 cm
Maximum exposure time	20 minutes



TECHNICAL SPECIFICATIONS

ULTRASUN i8

Power supply	3 x 400V + N + PE 50/60 Hz
Plug and cable (+airco)	32A CEE 5 x 4 mm ² (32A CEE 5 x 4 mm ²)
Power (+airco)	9.400W (10.400W)
Breaker/fuse (slow) (+airco)	3 x 25A (3 x 25A)
Minimum net weight ¹ (+airco)	230 kg (290 kg)
Minimum crated weight ¹ (+airco)	270 kg (360 kg)
Boxed dimensions (+airco)	227 x 114 x 125 cm (+ 120 x 80 x 99 cm)



¹ Minimum weight is based on an Ultrasun i8 with standard configuration. Machine specific weight information available on request.



Granaatstraat 6
7554 TR Hengelo
The Netherlands



+31 (0)74 2912215



info@ultrasun.nl



Ultrasoninternational.com