

STANDARD EQUIPPED WITH

ADDITIONAL OPTIONS



Control



Age Control



Electronic Ballast



TopCooler





VibraPlate





Rainbow Manager



Bluetooth Music System



Extraction Hose



CollaTan Lamps

AVAILABLE COLOUR



Cherry Red Metallic




- * When placing the Ultrasun i8e make sure that the device is surrounded by 10-15 centimetres of free space for air circulation.
- * The dimensions indicate an open Ultrasun i8e.

LAMP SPECIFICATIONS

ULTRASUN 18E LIMITED EDITION | COLLATAN

EU UV3	
Total Lamps	48 x Sunfit XXL3 200W CollaTan E-Tronic 200 cm
Maximum exposure time	20 minutes



ULTRASUN 18E LIMITED EDITION | UV

EU UV3	
Total Lamps	48 x Sunfit XXL3 200W E-Tronic 200 cm
Maximum exposure time	20 minutes

TECHNICAL SPECIFICATIONS

ULTRASUN 18E LIMITED EDITION

Power supply	3 x 400V + N + PE 50/60 Hz
Three phase	Socket Requirement 16 amps per phase TPN&E Female commando socket Trip Size 16 amps per phase C Type
Single phase	Socket Requirement 63 amps Female commando socket Trip Size 50 amps C Type
Power	9.200W
Minimum net weight ¹	225 kg



¹ Minimum weight is based on an Ultrasun i8e with standard configuration. Machine specific weight information available on request.











